



**Unit for disinfection and deodorisation of air in premises - comprises UV gas-discharge tube, high-voltage power supply, pulse generator, capacitor, transformer and control block, fan and pump**

**Patent Assignee:** MELITTA UF CO LTD

**Inventors:** ARKHIPOV V P; KAMRUKOV A S; KOZLOV N P

**Patent Family**

Patent Number	Kind	Date	Application Number	Kind	Date	Main IPC	Week	Type
RU 2092191	C1	19971010	RU 95110111	A	19950616	199822	B	

**Priority Applications (Number Kind Date):** RU 95110111 A ( 19950616)

**Filing Details**

Patent	Kind	Language	Page	Filing Notes	Application	Patent
RU 2092191	C1		7	A61L-009/20		

**Abstract:**

RU 2092191 C


A unit for disinfection and deodorisation of air in premises comprises housing (1) with fastened irradiator (5) containing UV source in the form of pulse-mode gas-discharge tube (6) mounted vertically in holder (7). The tube (6) is connected to power supply block (2) and placed in quartz casing (8) filled with distilled water (9) for cooling and the suppression of ozone-forming radiation. The tube (6) is filled with an inert gas as e.g. xenon under pressure close to atmospheric as e.g. 300-700 mm Hg. The power supply and control block (2) contain high-voltage d.c. generator (10), pulse generator for ignition (11), capacitor (12) and control circuit (13). The tube (6) is connected to the power supply and control block (2) through the pulse-mode transformer (14) with ferrite core; the primary winding is connected to the ignition generator (11), and the secondary winding is in series with capacitor (12) and tube (6). The discharge contour formed by capacitor (12), secondary winding of transformer (14) and gas-discharge tube (6) has the parameters which satisfy the relation:


the quantity  $(U^2/Adh)(C/L_0)^{1/2}$  is in the limits from 0.05 to 1, where U is the voltage on capacitor (V); C is the capacitance (F);  $L_0$  is the initial inductance of contour (H); d is the inner diameter of gas-discharge tube (m); h is the distance between electrodes of tube (m); and  $A=109$  is a constant coefficient ( $W/m^2$ ).

USE -The unit is useful in particular for disinfection of air in surgeries, outpatient units, clinics, hospitals, bacteriological laboratories, etc.

ADVANTAGE - The unit has reduced total energy dose because of high-Intensity pulsed UV-radiation of continuous spectrum, reduced time of processing to a few minutes, and improved safety and convenience.

Dwg.1/3





Derwent World Patents Index

© 2000 Derwent Information Ltd. All rights reserved.

Dialog® File Number 351 Accession Number 11832419